

Shut-off check valve combination 5150

- Dezincification resistant brass
- 15CU compression fittings
- Mixing valve
- Check valve
- Extended version with 100cc PEX pipe



Description

Shut-off check valve combination.

Construction

Shut-off check valve combination with mixing valve. Connection four compression fittings 15CU. Integrated check valve in the shut-off connecting valve. Possibility to connect a safety valve and/or vacuum valve. One plugged and one unplugged connection 1/2" on shut-off connecting valve. PEX pipe connects the mixing valve with the shut-off check valve.

Marking

Shut-off check valve: CR, flow control, arrow. Manufacturer name on hand wheel.
Mixing valve: CR, arrows showing inlet warm, inlet cold and outlet mixed water. Manufacturer's logotype and temperature control on hand wheel.

Maintenance

Shut-off check valve combinations are normally maintenance-free, but should be checked periodically.

Installation

Tighten nuts with a fixed spanner or wrench according to the prescribed installation instructions. Support sleeves must be used for all pipe types.

Technical data

Shut-off check valve

Body	Dezincification resistant brass CW625N
Seat gasket	EPDM
Stem gasket	EPDM

Mixing valve

Body	Dezincification resistant brass CW625N
O-ring	EPDM

Pipe

Plastic pipe	PEX
--------------	-----

Maximum working pressure: 10 bar
Maximum working temperature: +90°C
Minimum working temperature: +2°C
Control range +35 to +65°C ±5%

Item number	Description	Connection	Length	Height	Weight (kg per piece)
0551500000	Shut-off check valve combination 5150, 15CU	15CU	203	80	0,80

All dimensions in millimetres

Subject to technical changes and corrections without notice